




Collation shrink film leveraging Exxtend™ technology for advanced recycling



5-layer performance collation shrink film

Thickness: 35 µm

- Exceed S 9272ML
- Enable 3505MC
- Enable 4002MC
- ExxonMobil™ LD151HR
- ExxonMobil™ LD165BW1



ExxonMobil performance PE polymers deliver:

- Excellent toughness and stiffness
- Excellent shrink performance and package integrity
- Shelf appeal, brand visibility
- Includes certified-circular content*

*Through mass balance attribution

Polymer properties	Exceed S 9272ML	Enable 3505MC	Enable 4002MC	Test method* (based on)	Unit
Melt index (190°C/2.16 kg)	0.80	0.50	0.25	ASTM D1238	g/10 min
Density	0.920	0.935	0.938	ASTM D1505	g/cm ³

* For detailed product information, please consult the individual grade data sheet, available on our website: www.exxonmobilchemical.com. Values given are typical and should not be interpreted as specifications. Data generated by or on behalf of ExxonMobil.

Exxtend technology for advanced recycling

Exxtend can help widen the range of plastic materials that can be recycled and helps maintain the performance of material over multiple recycling loops. Product quality and performance of the certified-circular polymers are identical to polymers made from virgin raw materials, so customers can be confident when using them in existing applications.

Watch the video:



ExxonMobil
K2022
microsite:



Advancing sustainable solutions. Together.

For more information: exxonmobilchemical.com/pe
ExxonMobil Hub: EN11

©2022 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Product Solutions" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Product Solutions Company, Exxon Mobil Corporation, or any affiliate either directly or indirectly stewarded.



VAREX" WITH FILMATIC" V

Safe and easy – Efficient winding performance for VAREX"



Why VAREX" with FILMATIC" V?

The goal of this new winder generation was to achieve best-in-class winding performance, easy operation and excellent safety standards. The start of the winding process is critical, therefore we improved the surface winding from the beginning to very end of the roll. To make the highly complex winding process easy and reliable for all operators, W&H has developed a completely new human machine interface. Among other safety features, new light curtains and laser supported core alignment promoted meeting the highest international safety standards.

- Single point of operation reduces the risk of operator errors
- Integration of W&H automation and assistance modules
- Improved flexibility due to possible change of the winding direction
- Improved accessibility for easier maintenance
- Option for right angled cut with no foldback

Your advantages

- FILMATIC" V offers safe and easy winding performance for VAREX" blown film lines
- Highest level of process stability and flexibility with the most demanding applications
- Integration of automation and assistance modules like TURBOSTART and EASY2 CHANGE
- FILMATIC" V is easily retrofittable

Technical Data VAREX"

Line widths	1300 – 3600 mm
Number of film layers	1, 3, 5, 7, 9, 11
Extruder screw diameters	50, 60, 70, 90, 105, 120, 135 mm
Die diameters	160 – 900 mm
Raw materials	Biomaterials, recycling materials, PE, PP, EVOH, PA, Ionomers,
Winders	FILMATIC" V (surface/center/gap winder) FILMATIC" T (turret winder) FILMATIC" N (surface/center/gap winder)
Special equipment	Side gussets, Water bath, Annealing units, MDO, ...



Windmüller & Hölscher at K2022:
Hall 17 / A57

For more information: www.wuh-group.com